

CERTIFICATE OF COMPLIANCE

Certificate Number 20130212-E305816
Report Reference E305816-20060601
Issue Date 2013-FEBRUARY-12


Issued to: FUTURE DESIGN CONTROLS INC
7524 W 98TH PL
PO BOX 1196
BRIDGEVIEW IL 60454

This is to certify that representative samples of PROGRAMMABLE CONTROLLERS
See Addendum Page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: Industrial Control Equipment, UL 508
Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Listing Mark should be considered as being covered by UL's Listing and Follow-Up Service.

The UL Listing Mark generally includes the following elements: the symbol UL in a circle:  with the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20130212-E305816
Report Reference E305816-20060601
Issue Date 2013-FEBRUARY-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

LCD Touch screen programmable logic controllers, FDC-2010[#], FDC-2107i[#], FDC-2110i[#], FDC-610XH[#], FDC-612X[#], FDC-615X[#].

[#] - Series, may be followed by additional alphanumeric characters

ELECTRICAL RATINGS:

<u>Model</u>	<u>Supply Input Voltage</u>
FDC-2010 Series	24 V dc, Class 2

Power Inputs are limited to class 2 sources only.
All other signal inputs/outputs are limited voltage/current circuits.

Series No.	Rated Supply Voltage and Current
FDC-615X	24 V dc, Class 2, Maximum 1.6 A
FDC-2110i, FDC-610XH	24 V dc, Class 2, Maximum 1.25 A
FDC-612X	24 V dc, Class 2, Maximum 1.25 A
FDC-2107i	24 V dc, Class 2, Maximum 350 mA

Maximum Ambient Temperature: 50°C



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

