


BASE PRICING:

FDC - 2500 \$206.00



FDC-2500



Schedule A

1. POWER INPUT

- 4: 90 - 264VAC, 50/60 Hz N/C
- 5: 11 - 26VAC/VDC \$15.00
- 9: Special Order

2. SIGNAL INPUT

- 1: Input 1—Universal N/C
T/C, RTD or 4-20, 0-20mA
0-1V, 0-5V, 1-5V, 0-10VDC
- Input 2—CT/Analog Input/Event Input
CT: 0-50 Amp AC current transformer*
4/20, 0-20mA, 0-1V, 1-5V, 0-10VDC
(mA inputs require 250 OHM resistor)
Event Input
- 9: Special Order

3. OUTPUT 1

- 0: None N/C
- 1: Relay 2A/240VAC resistive (SPST) N/C
- 2: SSR Drive 5VDC @30mA N/C
- 3: 4-20 / 0-20VDC linear, max load 500 ohms \$26.00
- 4: 1-5 / 0-5VDC linear, min impedance 10K ohms \$26.00
- 5: 0-10VDC linear, min impedance 10K ohms \$26.00
- 6: Triac 1A/240VAC \$26.00
- C: SSR Drive 14VDC @40mA \$26.00
- 9: Special Order

4. OUTPUT 2 / ALARM 2 (control out is PID Cool only)

- 0: None N/C
- 1: Form A Relay 2A/240VAC resistive (N.O.) \$11.00
- 2: SSR Drive 5VDC @30mA \$11.00
- 3: 4-20 / 0-20mA linear, max load 500 ohms \$26.00
- 4: 1-5 / 0-5VDC linear, min impedance 10K ohms \$26.00
- 5: 0-10VDC linear, min impedance 10K ohms \$26.00
- 6: Triac 1A/240VAC \$26.00
- 7: Transmitter Power Supply 20VDC/25mA (isolated) \$26.00
- 8: Transmitter Power Supply 12VDC/40mA (isolated) \$26.00
- 9: Transmitter Power Supply 5VDC/80mA (isolated) \$26.00
- C: SSR Drive 14VDC @40mA \$26.00
- A: Special Order

5. ALARM 1

- 1: Logic Output, 5V/100 mA N/C

6. COMMUNICATIONS

- 0: None N/C
- 1: RS-485 \$70.00
- 2: RS-232** \$70.00
- 3: Retransmission: 0-20/4-20mA, isolated,
500 ohm load min \$80.00
- 4: Retransmission: i0-5/1-5 VDC, isolated,
10K ohm load min \$80.00
- 5: Retransmission: 0-10 VDC isolated,
10K ohm load min \$80.00
- 9: Special Order

7. SPECIAL ORDER

Leave Blank unless assigned a specific 2-character Special Order Code

Note: The last digit (codes 7) is typically left blank

*Order CT94-1 if heater break function is required.
CT-94 0-50AMP CT - \$30.00
**Alternative between RS-232 and Input 2.
Output 2: Configurable for PID cool (requires output #1 to be PID):
PID cool outputs: Relay, SSR or mA/VDC.
Configurable as Alarm #2: Relay & SSR output

DIN Rail Mount Adapter model DRA-32 refer to page 27