

CERTIFICATE OF COMPLIANCE

Certificate Number 20130212-E305816
Report Reference E305816-20120524
Issue Date 2013-FEBRUARY-12


Issued to: FUTURE DESIGN CONTROLS INC
7524 W 98TH PL
PO BOX 1196
BRIDGEVIEW IL 60454

This is to certify that representative samples of PROGRAMMABLE CONTROLLERS
See Addendum Page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: Industrial Control Equipment, UL 508
Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Listing Mark should be considered as being covered by UL's Listing and Follow-Up Service.

The UL Listing Mark generally includes the following elements: the symbol UL in a circle:  with the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20130212-E305816
Report Reference E305816-20120524
Issue Date 2013-FEBRUARY-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

LCD Touch Screen Human Machine Interface, FDC-0450, FDC-0730, FDC-0750, FDC-1050, FDC-1550, followed by 1 or 2, followed by 0 or 1, followed by 0 or 1, followed by 0 or 1, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, or 9, followed by 0, 1, or 2, followed by 0 or 1, maybe followed by blank or A thru Z, maybe followed by blank or A thru Z.

ELECTRICAL RATINGS:

Model	Input Rating
FDC-0450 Series	11-36 VDC, 10VA, 0.91A, Class 2 or 20.4-28.8 VDC, 7VA, 0.35A, Class 2
FDC-0730 Series	11-36 VDC, 12 VA, 1.09 A, Class 2 or 20.4-28.8 VDC, 8VA, 0.4A, Class 2 90-250 VAC, 47-63 Hz, 24VA, 0.27 A
FDC-0750 Series	11-36 VDC, 13VA, 1.18 A, Class 2 90-250 VAC, 47-63 Hz, 26 VA, 0.29 A
FDC-1050 Series	11-36 VDC, 15VA, 1.36A, Class 2 90-250 VAC, 47-63 Hz, 30VA, 0.33 A
FDC-1550 Series	11-36 VDC, 27VA, 2.46 A, Class 2 90-250 VAC, 47-63 Hz, 54VA, 0.6 A
Maximum Ambient Temperature	50°C
Environment Type	Suitable for mounting on the flat surface of Type 1 enclosure



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

