



BASE PRICING:

FDC - B41 \$165.00



Schedule A



1. POWER INPUT

- 4: 90-250VAC 50/60 HZ N/C
- 5: 11-26VAC/VDC \$15.00
- 9: Special Order

2. SIGNAL INPUT

- 1: Thermocouple: J,K,T,E,B,R,S,N,L N/C
RTD: PT100DIN & PT100 JIS
- 9: Other: (refer to manual for matrix codes for mA, VDC & mV)

3. OUTPUT 1

- 0: None N/C
- 1: Relay 2A/240VAC resistive (SPST) N/C
- 2: SSR Drive 5VDC @ 30mA N/C
- 3: 4-20/0-20mA linear, isolated, max load 500 ohms \$28.00
- 4: 1-5/0-5VDC linear, isolated, min impedance
10K ohms \$28.00
- 5: 0-10 VDC linear, isolated, min impedance
10K ohms \$28.00
- 6: Triac 1A/240VAC \$28.00
- C: SSR Drive 14VDC @ 40mA \$28.00
- 9: Special Order

4. OUTPUT 2 / Alarm 2 (control PID Cool only)

- 0: None N/C
- 1: Form A Relay 2A/240VAC resistive (SPST) \$12.00
- 2: SSR Drive 5VDC @ 30mA \$12.00
- 3: 4-20/0-20mA linear, isolated, max load 500 ohms \$28.00
- 4: 1-5/0-5VDC linear, isolated, min impedance
10K ohms \$28.00
- 5: 0-10VDC linear, isolated, min impedance
10K ohms \$28.00
- 6: Triac 1A/240VAC resistive \$28.00
- 7: Transmitter Power Supply 20VDC/25mA (isolated) \$28.00
- 8: Transmitter Power Supply 12VDC/40mA (isolated) \$28.00
- 9: Transmitter Power Supply 5VDC/80mA (isolated) \$28.00
- C: SSR Drive rated at 40mA/14VDC \$28.00
- A: Special Order

5. ALARM 1

- 0: None N/C
- 1: Form C Relay 2A/240VAC resistive (SPDT) \$12.00
- 9: Special Order

6. COMMUNICATIONS

- 0: None N/C
- 1: RS-485 Modbus RTU \$75.00
- 2: RS-232 Modbus RTU \$75.00
- 3: Retransmission: 0-20/4-20mA, isolated,
500 ohm load min \$90.00
- 4: Retransmission: 0-5/1-5VDC, isolated,
10K ohm load ,min \$90.00
- 5: Retransmission: 0-10VDC, isolated, 10K ohm load \$90.00
- 9: Special Order

**7. LENGTH OF FLAT CONNECTING CABLE:
CONTROL TO DISPLAY**

- 0: No Display Board N/C
- 3: Display Board with 300 mm connecting cable \$39.00
- 9: Special Order

Note: Display board and 300mm cable may be ordered as separate components

Part Number:	Description	Price
3020B41-00300B-00	display board	\$35.00
10353-20301-00-00	300mm cable	\$4.00

Output 2: Configurable for PID cool (requires output #1 to be PID):
PID cool outputs: Relay, SSR or mA/VDC.



P.O. Box 1196 Bridgeview, IL 60455
 888.751.5444 Sales 888.307.8014 Fax
 Technical Support: 866.342.5332
<http://www.futuredesigncontrols.com>